

MINIMUM & MAXIMUM SIZES								
CW			AW (Stay Bar)			Roto Crank		
	W	H		W	H	w	H	
MAXIMUM	3'-0"	8'-0"	MAXIMUM	4'-0"	3'-0"	3'-0"	2'-6"	
MINIMUM	1'-0"	1'-0"	MINIMUM	1'-0"	1'-0"	1'-6"	1'-6"	
FRENCH CW			HOPPER					
	W	H		W	H			
MAXIMUM	6'-0"	8'-0"	MAXIMUM	4'-0"	3'-0"	0'-0"	0'-0"	
MINIMUM	1'-10"	1'-0"	MINIMUM	1'-0"	1'-0"	0'-0"	0'-0"	
MINIMUM ARCHED TOP FULL RADIUS DIAMETER IS 3'-0"								
NOTE: INSATALL LIMITER AT TOP AND BOTTOM WHEN HEIGHT EXCEEDS 6'H ON CW AND FRENCH CW								

LATCH & FLUSHBOLT			
CW			
	W	H	
MAXIMUM	3'-0"	6'-0"	*1 Latch if < 3'-6" H *2 Latches if > 3'-6" H *Installation Height for unit must be known to confirm final latch location/height
MINIMUM	1'-0"	1'-0"	
FRENCH CW			
	W	H	
MAXIMUM	6'-0"	6'-0"	*1 Latch if < 3'-6" H *2 Latches if > 3'-6" H *Flushbolt at Top only if < 3'-6" (Inactive side) *Flushbolt at Top & Bottom if > 3'-6" (Inactive side) *Installation Height for unit must be known
MINIMUM	1'-10"	1'-0"	